


Operators for Roller Shutters



Part No. kW Amps Hp Voltage Phase Max. Door Size IP Rating Duty



Reversing Starter

Mechanical Logic

mDrive Operator | Low Cycle | Three Phase 415V

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
ML053M	0.37kW	1.55A	0.5Hp	415V	3ph	18m ²	IP44	LC
ML103M	0.75kW	2.30A	1.0Hp	415V	3ph	36m ²	IP44	LC
ML153M	1.10kW	2.55A	1.5Hp	415V	3ph	50m ²	IP44	LC

Control Options (not included)

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E006	GLMe2L	GLMe2
RG374-LB3E007	GLMe2L	GLMe2
RG374-LB3E007	GLMe2L	GLMe2

mDrive Operator | Low Cycle | Single Phase 240V

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
ML051M	0.37kW	3.4A	0.5Hp	240V	1ph	18m ²	IP44	LC
ML102M	0.75kW	6.0A	1.0Hp	240V	1ph	36m ²	IP44	LC

Reversing Starter	GLMe2L	GLMe2
RG375-LB1E008	GLMe2L	GLMe2
RG376-LB1E009	GLMe2L	GLMe2

mDrive Operator | High Cycle | Three Phase 415V

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH103M	0.75kW	1.95A	1.0Hp	415V	3ph	30m ²	IP44	HC

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E007	GLMe2L	GLMe2

mDrive Operator | High Cycle | Single Phase 240V


Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH102M	0.75kW	4.35A	1.0Hp	240V	1ph	30m ²	IP44	HC

Reversing Starter	GLMe2L	GLMe2
RG376-LB1E009	GLMe2L	GLMe2

When ordering please specify an "L" or an "R" at the end of every part number.
Clutch (C) option available. Refer additional pricing on page 6.

See page 18 for complete range of Reversing Starters.
See page 16 for complete range of GLMe2 Mechanical Logic Control options.

Specialty mDrive Operators for Roller Shutters



Part No. kW Amps Hp Voltage Phase Max. Door Size IP Rating Duty



Reversing Starter

Mechanical Logic

mDrive Operator | High Cycle | Three Phase 415V | D80 Flange (IP50)

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH103M8	0.75kW	1.95A	1.0Hp	415V	3ph	36m ²	IP50	HC

Control Options (not included)

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E007	GLMe2L	GLMe2

mDrive Operator | High Cycle | Three Phase 415V | Solenoid Brake (IP50)

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH103MB	0.75kW	1.95A	1.0Hp	415V	3ph	36m ²	IP50	HC

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E007	GLMe2L	GLMe2

mDrive Operator | High Cycle | Three Phase 415V | Dust Ignition Proof (IP66)

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH103MD	0.75kW	1.95A	1.0Hp	415V	3ph	36m ²	IP66	HC

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E007-EX	-	-

mDrive Operator | High Cycle | Three Phase 415V | Flameproof Exd (IP55)

Part No.	kW	Amps	Hp	Voltage	Phase	Max. Door Size	IP Rating	Duty
MH103MF	0.75kW	1.95A	1.0Hp	415V	3ph	36m ²	IP55	HC

Reversing Starter	GLMe2L	GLMe2
RG374-LB3E007-EX	-	-

When ordering please specify an "L" or an "R" at the end of every part number.

See page 18 for complete range of Reversing Starters.
See page 16 for complete range of GLMe2 Mechanical Logic Control options.

Popular Accessories

Reversing Starter

RG374
Page 18



Mechanical Logic Control (Light)

GLMe2L
Page 16



Mechanical Logic Control

GLMe2
Page 16



Mounting Plate Kit

SK1018
Page 22

